



MA-WM-A



MA-WM-B



MA-WM-M



MA-WM-N



MA-WM-AB / MA-WM-AC



MA-WM-D

IEC 60335 Standard, with CB certificate, SASO, KUCAS approved

SPECIFICATION / PERFORMANCE

Model	Cert Nr	Voltage	AC/Power (W)			Air Volume (CMH)		
			4 inch	5 inch	6 inch	4 inch	5 inch	6 inch
MA-WM-A	PBA	220	15	20	25	100	195	320
MA-WM-B	PBB	220	15	20	25	100	195	320
MA-WM-M	PBM	220	15	20	25	100	195	320
MA-WM-N	PBN	220	15	20	25	100	195	320
MA-WM-AB	PBAB	220	15	20	25	100	195	320
MA-WM-AC	PBAC	220	15	20	25	100	195	320
MA-WM-D	PBD	220	15	20	25	100	195	320

FIT OPENING / DIMANTIONS

Model	Opening (Inch)			Remark
MA-WM-A	4	5	6	
MA-WM-B	4	5	6	
MA-WM-M	4	5	6	
MA-WM-N	4	5	6	
MA-WM-AB	4	5	6	
MA-WM-AC	4	5	6	
MA-WM-D	4	5	6	

OPTIONS

- DC Motor up to 2.5W
- Time delay
- Humidity sensor